




DOMESTICS AND PROFESSIONAL POINT-OF-USE WATER DISPENSERS

POINT-OF- USE WATER DISPENSERS FOR HOUSEHOLD AND OFFICES - PROFESSIONAL POINT-OF-USE WATER DISPENSERS FOR BARS AND RESTAURANTS - CO2 CYLINDERS - PRESSURE REDUCER FOR CO2 CYLINDERS - WATER DISPENSERS

POINT-OF- USE WATER DISPENSERS FOR HOUSEHOLD AND OFFICES

DAPHNE Osmo Top

DAPHNE Osmo Top (Countertop) water dispenser : still water/cold water/sparkling water w/direct flow (tankless) RO-System




DAPHNE OSMO is a tankless reverse osmosis dispenser with direct production of permeate. It can easily be installed under the sink (Daphne OSMO Under version) or above any piece of furniture in your kitchen (DAPHNE OSMO Top version). Built with the best quality components according to D.M.174 /2004, characterized by an extremely compact and attractive design combined with superior performance, with reduced noise levels and almost zero thermal fluctuations. The system is equipped with an LCD display and a special cover for quick access to the filter compartment, which simplifies regular maintenance and service work. Allows for the continuous dispensing of still water at room temperature, still chilled and chilled sparkling water. TECHNICAL FEATURES - Power supply: 230 V 50 Hz - Power consumption: 200 W (in operation) - Dry cooling, hydraulic WITHOUT forced ventilation - Compressor 1/8 HP - Saturator 2.2 L - Sparkling water carbonator 2 L - Pump: Booster pump 900 GPD Super High Performance 48V 8bar* - *or 180 W motor and rotary vane pump on request

- Working pressure: 8 bar - Inlet water pressure: Min. 2, Max. 5 bar
- Operating temperature 2-35°C - Rejection rate: 95/98%
- Permeate/waste water ratio: 1/1 - Nominal osmotic water production at 25°C - Mod. with 2 2012 XL membranes 180 GPD 180 or 200 GPD 100 l/h (+/- 10%) - Mod. with 3 2012 XL membranes of 180 GPD 180 or 200 GPD 120 l/h (+/- 10%) - Cold water production 20 l/h with T. inlet 22°C and outlet 10°C - Permeate/effluent ratio: 1/1 - Pump start delay - TDS control BYPASS - External pressure gauge - Electronic temperature control
- Dimensions: H 39 x W 18.7 x D 49 cm - Weight: 25 ELECTRONIC CONTROL - Electronic function control unit - Backlit display with soft-touch adjustment buttons - Filter change alarm - Water leak alarm with automatic blocking in case of leakage - Automatic washing of the membranes adjustable every 6-8-12 hours at rest

Item-Nr:	Description:
DOTAVK1B200	Daphne Osmo Top Ambient/cold/sparkling water dispenser with direct flow reverse osmosis system Countertop

DAPHNE Osmo Under

DAPHNE Osmo Under (Undercounter) water dispenser : still water/cold water/sparkling water w/direct flow (tankless) RO-System




DAPHNE OSMO is a tankless reverse osmosis dispenser with direct production of permeate. It can easily be installed under the sink (Daphne OSMO Under version) or above any piece of furniture in your kitchen (DAPHNE OSMO Top version). Built with the best quality components according to D.M.174 /2004, characterized by an extremely compact and attractive design combined with superior performance, with reduced noise levels and almost zero thermal fluctuations. The system is equipped with an LCD display and a special cover for quick access to the filter compartment, which simplifies regular maintenance and service work. Allows for the continuous dispensing of still water at room temperature, still chilled and chilled sparkling water. TECHNICAL FEATURES - Power supply: 230 V 50 Hz - Power consumption: 200 W (in operation) - Dry cooling, hydraulic WITHOUT forced ventilation - Compressor 1/8 HP - Saturator 2.2 L - Sparkling water carbonator 2 L - Pump: Booster pump 900 GPD Super High Performance 48V 8bar* - *or 180 W motor and rotary vane pump on request

- Working pressure: 8 bar - Inlet water pressure: Min. 2, Max. 5 bar
- Operating temperature 2-35°C - Rejection rate: 95/98%
- Permeate/waste water ratio: 1/1 - Nominal osmotic water production at 25°C - Mod. with 2 2012 XL membranes 180 GPD 180 or 200 GPD 100 l/h (+/- 10%) - Mod. with 3 2012 XL membranes of 180 GPD 180 or 200 GPD 120 l/h (+/- 10%) - Cold water production 20 l/h with T. inlet 22°C and outlet 10°C - Permeate/effluent ratio: 1/1 - Pump start delay - TDS control BYPASS - External pressure gauge - Electronic temperature control
- Dimensions: H 39 x W 18.7 x D 49 cm - Weight: 25
- ELECTRONIC CONTROL - Electronic function control unit - Backlit display with soft-touch adjustment buttons - Filter change alarm - Water leak alarm with automatic blocking in case of leakage - Automatic washing of the membranes adjustable every 6-8-12 hours at rest

Item-Nr:	Description:
DOUAVK1B200	Daphne Osmo Under Ambient/cold/sparkling water dispenser with direct flow reverse osmosis system

DAPHNE Micro Top

DAPHNE Micro Top (Countertop) water dispenser : still water/cold water/sparkling wate without pre-filtration



DAPHNE MICRO is a water cooling dispenser with pre-filtration. It can be easily installed under the sink (DAPHNE Micro Under version) or above any piece of furniture in your kitchen (DAPHNE MICRO Top version). Built with the best quality components according to D.M.174 /2004, characterized by an extremely compact and attractive design combined with superior performance, with reduced noise levels and almost zero thermal fluctuations. The system is equipped with an LCD display and a special cover for quick access to the filter compartment, which simplifies regular maintenance and service work. Allows continuous dispensing of room temperature and chilled still water as well as chilled sparkling water. All connections are at the back: water pipe inlet, CO2 cylinder inlet, natural cold water outlets, sparkling cold water and natural room temperature water outlets.


TECHNICAL FEATURES - Dry cooling, hydraulic WITHOUT forced ventilation - 1/8 Hp compressor - 2.2 l saturator - 2 l sparkling water carbonator - Pump: Booster 900 GPD Super High Performance 48V 8bar* - *or 180 W motor and vane pump on request - Nominal water production at 25°C and pressure 3.5 bar: approx 2 l/h - Production of cold water 20 l/h with T. inlet 22° C and outlet 10° C - External pressure gauge - Electronic temperature control - Dimensions: H 39 x W 18.7 x D 49 cm - Weight: 23 kg **ELECTRONIC CONTROL** - Electronic function control unit - Backlit display with soft-touch adjustment buttons - Filter change alarm - Water leak alarm with automatic blocking in case of leakage

Item-Nr:	Description:
----------	--------------

DMTAVK1B200	Daphne Micro Top Ambient/cold/sparkling water dispenser w/microfiltration Countertop version
-------------	--

DAPHNE Micro Under

DAPHNE Micro Under (Undercounter) water dispenser : still water/cold water/sparkling water with and without pre-filtration



DAPHNE MICRO is a water cooling dispenser with pre-filtration. It can be easily installed under the sink (DAPHNE Micro Under version) or above any piece of furniture in your kitchen (DAPHNE MICRO Top version). Built with the best quality components according to D.M.174 /2004, characterized by an extremely compact and attractive design combined with superior performance, with reduced noise levels and almost zero thermal fluctuations. The system is equipped with an LCD display and a special cover for quick access to the filter compartment, which simplifies regular maintenance and service work. Allows continuous dispensing of room temperature and chilled still water as well as chilled sparkling water.


TECHNICAL FEATURES - Dry cooling, hydraulic WITHOUT forced ventilation - 1/8 Hp compressor - 2.2 l saturator - 2 l sparkling water carbonator - Pump: Booster 900 GPD Super High Performance 48V 8bar* - *or 180 W motor and vane pump on request - Nominal water production at 25°C and pressure 3.5 bar: approx 2 l/h - Production of cold water 20 l/h with T. inlet 22° C and outlet 10° C - External pressure gauge - Electronic temperature control - Dimensions: H 39 x W 18.7 x D 49 cm - Weight: 23 kg **ELECTRONIC CONTROL** - Electronic function control unit - Backlit display with soft-touch adjustment buttons - Filter change alarm - Water leak alarm with automatic blocking in case of leakage

Item-Nr:	Description:
----------	--------------

DMUAVK1B200	Daphne Micro Under Ambient/cold/sparkling water dispenser w/microfiltration Undercounter version
-------------	--

DAPHNE Plain Top

DAPHNE Top (Countertop) water dispenser : still water/cold water/sparkling water with and without pre-filtration



DAPHNE is a water cooling dispenser that can be easily installed under the sink (DAPHNE Under version) or above any piece of furniture in your kitchen (DAPHNE Top version). Built with the best quality components according to D.M.174 /2004, characterized by an extremely compact and attractive design combined with superior performance, with reduced noise levels and almost zero thermal fluctuations. The system is equipped with an LCD display and a special cover for quick access to the filter compartment, which simplifies regular maintenance and service work. Allows continuous dispensing of room temperature and chilled still water as well as chilled sparkling water.


TECHNICAL FEATURES - Dry cooling, hydraulic WITHOUT forced ventilation - 1/8 Hp compressor - 2.2 l saturator - 2 l sparkling water carbonator - Pump: Booster 900 GPD Super High Performance 48V 8bar* - *or 180 W motor and vane pump on request - Nominal water production at 25°C and pressure 3.5 bar: approx. 2 l/h - Production of cold water 20 l/h with T. inlet 22° C and outlet 10° C - External pressure gauge - Electronic temperature control - Dimensions: H 39 x W 18.7 x D 49 cm - Weight: 23 kg **ELECTRONIC CONTROL**
 - Electronic function control unit - Backlit display with soft-touch adjustment buttons - Filter change alarm - Water leak alarm with automatic blocking in case of leakage

Item-Nr:	Description:
----------	--------------

DVTAVK1B200	Daphne Plain Top Ambient/cold/sparkling water dispenser without pre-filtration Countertop version
-------------	---

DAPHNE Plain Under

DAPHNE Under (Undercounter) water dispenser : still water/cold water/sparkling water without pre-filtration



DAPHNE is a water cooling dispenser that can be easily installed under the sink (DAPHNE Under version) or above any piece of furniture in your kitchen (DAPHNE Top version). Built with the best quality components according to D.M.174 /2004, characterized by an extremely compact and attractive design combined with superior performance, with reduced noise levels and almost zero thermal fluctuations. The system is equipped with an LCD display and a special cover for quick access to the filter compartment, which simplifies regular maintenance and service work. Allows continuous dispensing of room temperature and chilled still water as well as chilled sparkling water.


TECHNICAL FEATURES - Dry cooling, hydraulic WITHOUT forced ventilation - 1/8 Hp compressor - 2.2 l saturator - 2 l sparkling water carbonator - Pump: Booster 900 GPD Super High Performance 48V 8bar* - *or 180 W motor and vane pump on request - Nominal water production at 25°C and pressure 3.5 bar: approx. 2 l/h - Production of cold water 20 l/h with T. inlet 22° C and outlet 10° C - External pressure gauge - Electronic temperature control - Dimensions: H 39 x W 18.7 x D 49 cm - Weight: 23 kg **ELECTRONIC CONTROL**
 - Electronic function control unit - Backlit display with soft-touch adjustment buttons - Filter change alarm
 - Water leak alarm with automatic blocking in case of leakage

Item-Nr:	Description:
----------	--------------

DVUAVK1B200	Daphne Plain Under Ambient/cold/sparkling water dispenser without pre-filtration Undercounter version
-------------	---

DAPHNE Plain Under - Version MINI

DAPHNE MINI Under (Undercounter-reduced version) water dispenser : still water/cold water/sparkling water without pre-filtration



DAPHNE is a water cooling dispenser that can be easily installed under the sink (DAPHNE Under version) or above any piece of furniture in your kitchen (DAPHNE Top version). Built with the best quality components according to D.M.174 /2004, characterized by an extremely compact and attractive design combined with superior performance, with reduced noise levels and almost zero thermal fluctuations. The system is equipped with an LCD display and a special cover for quick access to the filter compartment, which simplifies regular maintenance and service work. Allows continuous dispensing of room temperature and chilled still water as well as chilled sparkling water.

TECHNICAL FEATURES - Dry cooling, hydraulic WITHOUT forced ventilation - 1/8 Hp compressor - 2.2 l saturator - 2 l sparkling water carbonator - Pump: Booster 900 GPD Super High Performance 48V 8bar* - *or 180 W motor and vane pump on request - Nominal water production at 25°C and pressure 3.5 bar: approx. 2 l/h - Production of cold water 20 l/h with T. inlet 22° C and outlet 10° C - External pressure gauge - Electronic temperature control - Dimensions: H 39 x W 18.7 x D 49 cm - Weight: 23 kg **ELECTRONIC CONTROL**
 - Electronic function control unit - Backlit display with soft-touch adjustment buttons - Filter change alarm
 - Water leak alarm with automatic blocking in case of leakage

Item-Nr:	Description:
DPUAVK1B00M	Daphne Plain Under (Mini) Undercounter Ambient/cold/sparkling water dispenser without pre-filters

DAPHNE - Accessories

DAPHNE - Accessories for dispensers DAPHNE Series



Item-Nr:	Description:
DZA	DAPHNE - various accessories - prices on request
DZACOLBL	Support cabinet for water dispenser Daphne Top (Osmo, Micro, Plain)

DAPHNE - Spare parts

DAPHNE -Spare parts for dispensers DAPHNE Series



Item-Nr:	Description:
DZR	DAPHNE - Spare parts - prices on request

Kyra TOP Ice Hermetic

Water dispenser "Kyra Top Ice Hermetic" countertop plain,cold,soda- hermetic ice block



Cooling system: hermetic ice bench Water flow at ambient temperature V
 Cold water flow rate 15 l / h
 Sparkling water flow 25 l / h
 Booster pump (made in Italy) 120 l / h
 Hermetic bench 3 l - Carbonator 2,5 l
 Absorption 77 W Refrigeration Power 155 W
 Operating pressure 3 bar
 Power supply 230V - 50Hz - Compressor 1/12 HP
 R134a gas 78 g.
 Noise <65 db.

Dimensions (mm) 170 x 320 x h430
 Weight 16,0 kg - Materials: Side panels Stainless steel ABS front panel
 Special voltages on request
 Customized equipment on request

Item-Nr:	Description:
KY3TOH025ICEB	Kyra Top Ice Hermetic Countertop Water dispenser (Black)- cool plain / cold sparkling / room temperatureplain-
KY3TOH025ICEW	Kyra Top Ice Hermetic Countertop Water dispenser (White)- cool plain / cold sparkling / room temperatureplain-

Kyra UNDER Ice Hermetic

**Water dispenser "Kyra Under Ice Hermetic"
undercounter-plain,cold,soda-hermetic ice block**



Cooling system: hermetic ice bench Water flow at ambient temperature V
 Cold water flow rate 15 l / h
 Sparkling water flow 25 l / h
 Booster pump (made in Italy) 120 l / h
 Hermetic bench 3 l - Carbonator 2,5 l
 Absorption 77 W Refrigeration Power 155 W
 Operating pressure 3 bar
 Power supply 230V - 50Hz - Compressor 1/12 HP
 R134a gas 78 g.
 Noise <65 db.

Dimensions (mm) 170 x 320 x h430
 Weight 16,0 kg - Materials: Side panels Stainless steel ABS front panel
 Special voltages on request
 Customized equipment on request

Item-Nr:	Description:
KY3UNH025ICE	Kyra Under ICE Hermetic Undercounter Water dispenser - cool plain / cold sparkling / room temperatureplain-

PROFESSIONAL POINT-OF-USE WATER DISPENSERS FOR BARS AND RESTAURANTS

GLACIER 60

Professional water dispenser Soda "GLACIER 60" 60 l/h cold,plain room, sparkling water



Item-Nr:	Description:
GL3TAFRU060ICE	Clacier 60 Professional countertop water dispenser 60 l/h - w/water faucets, cool plain / cold sparkling / room
GL3UAFRU060ICE	Clacier 60 Professional cundercounter water dispenser for mechanical tap 60 l/h - w/water faucets, cool plain /

GLACIER 90

Professional water dispenser Soda "GLACIER 90" 90 l/h cold,plain room, sparkling water



Item-Nr:	Description:
GL3TAFRU090ICE	Clacier 90 Professional countertop water dispenser 90 l/h - w/water faucets, cool plain / cold sparkling / room
GL3UAFRU090ICE	Clacier 90 Professional cundercounter water dispenser for mechanical tap 90 l/h - w/water faucets, cool plain /

GLACIER 120

Professional water dispenser Soda "GLACIER 120" 120 l/h cold,plain room, sparkling water



Item-Nr:	Description:
GL3TAFRU120ICE	Clacier 120 Professional countertop water dispenser 120 l/h - w/water faucets, cool plain / cold sparkling / room
GL3UAFRU120ICE	Clacier 120 Professional cundercounter water dispenser for mechanical tap 120 l/h - w/water faucets, cool plain /

CO2 CYLINDERS

CO2-C

Co2 Cylinders for Soda carbonation system



Item-Nr:	Description:
BOCO2N20	co2 Cylinder 2 Kg (new) w/ Tulip style handle
BOCO2N40	co2 Cylinder 4 Kg (new) w/ Tulip style handle

PRESSURE REDUCER FOR CO2 CYLINDERS

CO2-PRESSURE REDUCER EG02

Pressure reducer EG02 for Co2 Cylinders



Mod. EG02 for rechargeable CO2 Cylinders
 Technical Specifications Material: Aluminum Alloy HR
 Treatment: Anodized (Anthracite)
 Inlet pressure: 10 to 160 bar
 Outlet pressure: 0-5.5 bar [adjustable]
 Gauges: DN 40 low pressure [0-10 bar]

Safety: Overpressure
 Attack cylinder: Extension Adapter EU 21.8X1/14 "for refillable
 Output: 1/8 female
 Flow rate: 15 l / min
 Size: 74X 84 Ø 38 mm
 Weight: 195 g

Item-Nr:	Description:
GRRIC2EADA	Extension adapter M11x1 → W21.8x1/14 "CO2 cylinders
RIDCO2DRS1MST	Pressure reducer for CO2 Cylinders "DRS" 6 BAR with 1 gauge
RIDCO2DRS2MST	Pressure reducer for CO2 Cylinders "DRS" 6 BAR with 2 gauges LP/HP EU21.8X1/14" AL/GREY

WATER DISPENSERS

WAC MOD."ELECTRA"

Water dispensers "ELECTRA" Series hot/cold/ambience POU



Water dispenser with streamlined shape, three buttons for dispensing hot, cold and room temperature water. Featuring special safety lock particularly suitable for children. Functions : Hot water - Cold Water - Room temperature Water - Power supply AC220V-AC240 V 50-60 Hz
 Dimensions : 104x33,5x36,5 cm Package dimensions: 108x37,6x40,5cm Net weight: 20,5 Kg Gross weight : 22,5 Kg

Hot water features - Tanks volume : 0,5/1,5 L Power consumption: 1150W/500W Capacity: 85°C -95°C 8 l/h Heating system: Bottom heating, band heating ,Immersion heating Cold water features - Refrigerant : R134a Tanks volume: 3,3L Consumption : 85W Capacity: 5°C-10°C 2 l/h

Item-Nr:	Description:
WCACH01BW	Glass holder for water cooler ELECTRA Series
WCAEL01FCPOU	Water cooler Mod Alcyone (Hot/cold water) Point Of Use for purified water w/clips for filtration system assembly

WAC MOD."SPHERA"

Water dispensers "SPHERA" Series hot/cold/ambience POU



Water dispenser with streamlined shape, three buttons for dispensing hot, cold and room temperature water. Featuring special safety lock particularly suitable for children. Functions : Hot water - Cold Water - Room temperature Water - Power supply AC220V-AC240 V 50-60 Hz
 Dimensions : 110x34x36cm Package dimensions: 116x40x42cm Net weight: 20,5 Kg Gross weight : 22,5 Kg

Large lead disèlay screen Separate holding tank Ambient 5 L Hot 1,8 L Cold 1,8 L Cooling by compressor

Item-Nr:	Description:
WCASP01FCPOU	Water cooler Mod Sphera- (Hot/cold water) Point Of Use for purified water w/clips for filtration system assembly
WCASP01FCUF	Water cooler Mod Sphera- (Hot/cold water) Point Of Use for purified water with ultrafiltration system